



FAL Automatic Rifle is a gas operated weapon which shows closed bolt and it is positively bolted. It is a light weapon and it allows the immediate performance of an intense fire. It is usually operated on semi-automatic mode (single shot). The automatic shot can be performed under good conditions of stability.

ATTACHEMENTS

With bipod and blank firing - device



AMMUNITION:

Cal. 7.62 x 51 mm Cartridges:

- NATO with "C" STANDARD BULLET - FMK 1 Mod. 0
- NATO with "P" ARMOUR-PIERCING BULLET - FMK 2 Mod. 0
- NATO with "PI" ARMOUR-PIERCING INCENDIARY BULLET - FMK 3 Mod. 0
- NATO with "T" TRACER BULLET - FMK 4 Mod. 0
- NATO with "I" TRAINING BULLET - FMK 12 Mod. 0
- "F" BLANK (PLASTIC CARTRIDGE CASE)
- NATO with "R" TARGETING BULLET - FMK 5 Mod. 0
- "LGR" GRENADE LAUNCHER - FMK 11 Mod. 0
- "EC" SPECIAL for COMPETITION - FMK 9 Mod. 0



TECHNICAL FEATURES	FAL IV	FAL PARA III
WEAPON: Overall length without bayonet Weight without magazine Overall length without bayonet with stock folded	1 090 mm 4 325 gr Butt stock	1 092 mm 4 000 gr 847 mm
MAGAZINE: Loading capacity Weight of the empty magazine Weight of the loaded magazine	20 cartridges 250 gr 730 gr	20 cartridges 250 gr 730 gr
BARREL: Length Number of grooves Direction of the twist Pitch of rifling	533 mm 4 right-handed twist 305 mm	533 mm 4 right-handed twist 305 mm
AIMING DEVICE: Rear sight	Two blades gauged for 150/250 m	Two blades gauged for 150/250 m
RATE OF FIRE: On automatic mode (theoretical) On automatic mode (practical) On semi-automatic mode	650/700 rounds/min 120 rounds/min 60 rounds/min	650/700 rounds/min 120 rounds/min 60 rounds/min



DIRECCION GENERAL DE FABRICACIONES MILITARES

Av. Cabildo 65 - 1426 Buenos Aires

República Argentina

Tels. 771-1940 / 1678

Télex 24746 GGV AD - AR

FAX 54 - 1 - 771 - 1940

**CALIBER 7.62 × 51 mm NATO
FAL IV LIGHT AUTOMATIC RIFLE**



